

Click Here



Rca dual alarm clock radio manual

Power Supply: 120V ~ 60Hz • Keep your unit away from humid Power Consumption: 4 Watts areas and abnormally hot places. Trademark(s) © Registered Marke(s) © Depo  e(s) Marca(s) © Registrada(s) www.rca.com Printed in China / Impreso en China 5629 7910 (EN/F/E) Clock Setting Clock US Time Zones 1. Press REV or FWD to set therespective wake time. If you find our work useful, please pitch in. Replace the compartment door. Additionally, the clock radio offers a snooze ... The descriptions and characteristics in this owner's manual are for the purpose of general reference only and not View and Download RCA RP3722 operating instructions manual online. If this equipment does cause interference to cord strain relief. It helps reducing (MST) drift on FM reception and keeping the radio locked in on the FM station to which (CST) it is tuned. The time be used repeatedly up to 30 minutes "SmartSnooze TM Operation") decrements or increments will follow (default: 9 minutes). Built-In AFC The Built In Automatic Frequency Control (AFC) works only on FM. Press and hold SLEEP on the top of the thunit and use REV or FWD toset the duration up to 2 hours. Wake Function Wake Function Setting Wake Time Turning Off the Wake Alarm or SmartSnooze This unit allows two wake times to be set. Connect your auxiliary source (e.g. mp3player) to the AUX input jack on the right2. In accordance with FCC requirements, changes and try to insert it the other way. Tocut the power supply off, the powerOFF - turns the unit on or off.FWD - sets time (increases value).SNOOZE - enters snooze mode where thealarm will quiet but sound again once the REV - sets time (decreases value).RADIO/AUX - selects radio or AUX mode.WAKE - OFF - activates and sets wake /WAKE1/WAKE2/ - slide switch to setwake 1. Wake 2 and clock time.NAP - activates nap function.SLEEP - activates sleep function.BRIGHTNESS - selects display brightness.TIME ZONE - slide to select time zonecorresponds to your location.DST - turns daylight saving function on or off.AM/FM - selects between AM and FM bands.-VOLUME+ - adjusts volume.TUNING - selects radio frequencies.Before You Plug for PowerYou may slide the TIME ZONE selector atthe back of the unit to Eastern (EST),Central (CST), Mountain (MST) or Pacific(PST) (refer to the maps on the right). You can slide the DST switch at the backof the unit to turn on/ off in areasobserving/ not observing such timeWARNING: Please avoid playing withthese buttons after entering theYou do not have to set the clock time as abuilt-in automatic time set system isequipped in this clock powered by 3V (2X AA batteries, included). N O U S E R - WARNING SIGN Communications Commission has prepared a W A R N I N G S I G N ALERTING YOU OFF techniques. AUX IN - AUX input jack. Clock Top View Before You Plug for Power OFF - turns the unit on or off. Piso 13.Col. Delegaci  n Cuauht  mocTel  fono: 52-55-11-020360The AC power plug is polarized(one blade is wider than theother) and only fits into ACpower outlets one way. Connect your auxiliary source (e.g. mp3 player) to the AUX input jack on the right side of the unit. of the unit to turn on/ off in areas /WAKE1/WAKE2/ - slide switch to set observing/ not observing such time Wake 1, Wake 2 and clock time. available when /WAKE1/ /WAKE1/ /WAKE1/ /WAKE1/ /WAKE1/ 2. The time decrements orincrements will follow by a faster ratethan you press and hold the buttons.Switching Off Wake FunctionPress WAKE - OFF 1 or 2 repeatedly onto the top of the unit until no wake mode iconIn sleep mode, you can set the duration(up to 2 hours) before the radio turn off. SLEEP - activates sleep function. All you have to do is to plug this clock for power and current time will be shown automatically. RCA RP5420: User Manual. Never use solvents. Replace the compartment door.Note: we recommend that you replace thebatteries every 2-3 years.Es importante leer este manual antes de usar por vez primera su equipo. 1 - Wake 1 by alarm 1. After this, the wake by a faster rate when you press and function will turn off until the next day, equipped in this clock powered by 3V (2 X AA batteries, included). TO RAIN OR MOISTURE. Do not loosen or throw this screw away! radio or television reception (which you can determine by unplugging the unit), try to correct For Your Records the interference by one or more of the following measures: 1 In the event that service should be required, you • Re-orient the receiving antenna (that is, the may need the model number. To check the remaining duration before the radio turns off, press and hold SLEEP. Setting Time Zone FWD - sets time (increases value). Daylight Saving WAKE - OFF - activates and sets wake You can slide the DST switch at the back function. We'd be deeply grateful if you'd join the one in a thousand users that support us financially. In order to provide you with the highest quality product, we may make changes or modificationswithout prior notice. Press "Switching off Wake Function", M  xico, D.F. • The apparatus shall not be exposed to Telefono: 52-55-11-020360 dripping or splashing and on that RFC: CTM-980723-KS5 objects filled with liquids, such as vases, shall be placed on the apparatus. Piso 13. Press the ON/OFF button on the top of the unit to turn on the radio. RP3722 clock radio pdf manual download. Press again to switch back to listen to the radio. (seeTo turn off the wake alarm or radiocompletely, press OFF, you switch off the Wake function (see 3. • The rating plate is located at the bottom cabinet of apparatus. The alarm or radio will be on 2. Delegaci  n Cuauht  moc C.P. 06700. In the spacebelow, record the date and place of purchase: This product should be serviced only by thosepecially trained by thoseprofessionally trained in appropriate servicingtechniques. Instead, we're powered by online donations averaging about \$15. Press and hold NAP on the top of the thunit and use REV or FWD toset the duration up to 2 hours (eachpress decreases or increases duration2. Press RADIO/AUX to switch to listen to auxiliary source. Turn on the unit and your auxiliary source.3. Press RADIO/AUX to switch to listen toauxiliary source. The wake alarm orradio will activate again the next day unlessyou switch off the Wake function (see "Switching off Wake Function") This operation allows extra sleep timeafter the wake function is on. • No naked flame sources, such as lighted candles, should be placed on the apparatus. Selecting Wake Source Tip: The unit equips with GRAD- GRAD- GRAD- U-WAKE feature, the alarm tone U-WAKE U-WAKE U-WAKE U-WAKE You may be woken up by radio or alarm. P.O. Box 1976 Indianapolis, IN 46206 - 1976   2006 Thomson Inc. change. Radio Selecting Radio Mode Press RADIO/AUX to switch on radio. Remove battery compartment door(located at the bottom of the radio)by applying thumb pressure to thetab on battery door and then lift thedoor out and off the cabinet.2. Insert 2 AA batteries (included).3. Auto Clock Set TIME ZONE - slide to select time zone corresponds to your location. The alarm Press SNOOZE on the top of the unit. Listening to Auxiliary Source 1. Roma. The on the top of the unit to WAKE 1 or will be off by pressing SNOOZE, NAP, wake alarm or radio will be switched off WAKE 2 position. AM Antenna A built-in ferrite rod antenna eliminates the need for an outside antenna for AM reception. • Plug the unit into a different wall outlet so Place of Purchase: that the unit and the equipment receiving interference are on different branch circuits. Slide BRIGHTNESS SWITCH on the back of the unit to HI (high) or LO (low) position to adjust the brightness. If it still does not fit, contact a qualified or modifications not expressly approved by Thomson Inc. After AC power is restored(reconnected), the Digital Display will blink toindicate that power was interrupted and youshould readjust the time and alarm settings.Power is fed to the unit evenwhen it is not functioning. Turn on the unit and your auxiliary source. • Minimum distances (2cm) around the apparatus for sufficient ventilations. Operation is subject to the following twconditions: (1) This device may not cause harmfulinterference, and (2) this device must accept anyinterference received, including interference that may cause undesired operation. In accordance with FCC requirements, changesor modifications not expressly approved byThomson Inc. Do not loosen or throw this in the event that service should be required, youmay need the model number. The AUX indicator on the front will turn on, function of alarm still occurs during the power interruption if remaining battery power is adequate. • Attention should be drawn to the environmental aspects of battery disposal. View and Download RCA RP5420 user manual online. The alarmwill be off by pressing SNOOZE, NAP,SLEEP, REV or FWD until thesnooze period is over. The time decrements or increments will follow by a faster rate when you press and hold the buttons. To cut the power supply off, the power Battery Back-Up Operation cable must be unplugged. • The use of apparatus in moderate Alvaro Obreg  n No. 151. Press and hold SNOOZE. Thewake alarm or radio will be switched offtemporarily. This clock radio is equipped with a memory holding system that can be powered with 2 "AA" batteries (included). Thetime decrements or increments willfollow by a faster rate when you pressNote: The radio will be switched on.This function wakes you up after a shortperiod of time (from 10 minutes to 21. When the alarm sounds, press SNOOZE to switch it off. Brand: RCA • Do not use your System immediately Model: RP5420 after transporting it from a cold place to a warm place, as condensation may Electrical Consumption cause the system to malfunction. (RF) energy, and if not installed and used properly, this equipment may cause interference Caution: The screw fastening power cord at the bottom enclosure is served as a means of power to radio and television reception. BRIGHTNESS - selects display brightness. To cancel the sleep function, press SNOOZE or OFF. Slide BRIGHTNESS switch on the back of the unit to HI (high) or LO (low)position to adjust the brightness.Press RADIO/AUX to switch on radio.Slide the AM/FM switch on the back of the thunit to select FM or AM band.Turn the TUNING knob on the right of the thunit to adjust radio frequency. NAP - activates nap function. Slide the switch /WAKE1/WAKE2/ after the wake function is on. For instructions on how to obtainservice, refer to the warranty included in thisPower Supply: 120V ~ 60HzPower Consumption: 4 WattsComercializadora Thomson de M  xico, S.A. de C.V.Alvaro Obreg  n No. 151. If it still does not fit, contact a qualifiedelectrician to change the outlet, or use adifferent one. Please specify stock number 004-000-00345-4 when ordering WARNING: TO PREVENT FIRE OR ELECTRICAL The descriptions and characteristics in this owner's manual are for the purpose of general reference only and not SHOCK HAZARD, DO NOT EXPOSE THIS PRODUCT as a guarantee. Press again to switchback to listen to the radio.Tip: The unit equips with U-WAKE feature, the alarm tonevolume will increase gradually toits maximum in about 30 to 45turning the Wake Alarm orPress SNOOZE on the top of the unit. RADIO/AUX - selects radio or AUX mode. Maintenance Clean the unit with a soft cloth, or a damp chamois leather. Tuning the Radio Turn the TUNING knob the right of the unit to adjust radio frequency. Press and hold NAP on the top of the REV or FWD until the unit and use set the duration up to 2 hours (each press decreases or increases duration) Note: SmartSnooze TM is only by 10 minutes). the top of the unit until no wake mode icon shows on the display. CAUTION If these measures do not eliminate the RISK OF ELECTRIC SHOCK Service Information interference, please consult your dealer or an DO NOT OPEN experienced radio/television technician for T H E L I G H T N I N G CAUTION: TO REDUCE THE THE EXCLAMATION This product should be serviced only by those FLASH AND ARROW- RISK OF ELECTRIC SHOCK, POINT WITHIN THE additional suggestions. 4. Please specifystock number 004-000-00345-4 when orderingIndianapolis, IN 46206 - 1976Trademarks)    RegisteredPrinted in China / Impreso en ChinaComercializadora Thomson de M  xico, S.A. de C.V.Alvaro Obreg  n No. 151. T H E P R O D U C T. In the space antenna for the radio or television that is below, record the date and place of purchase: "receiving" (the interference). Press and hold SLEEP on the top of the 1 - Wake 1 by radio 2 - Wake 2 by alarm 2 - Wake 2 by radio Checking Wake Time Slide the switch /WAKE1/WAKE2/ on the top of the unit to WAKE 1 or WAKE 2 position to check the currently set wake time. Ecology Help protect the environment - we recommend that you dispose of used batteries by putting them into specially designed receptacles. The wake alarm or hour and minute time flashes when radio will activate again the next day when you are setting the time. R E F E R S E R V I C I N G I M P O R T A N T Service, refer to the warranty included in this " D A N G E R O U S T O Q U A L I F I E D S E R V I C E I N S T R U C T I O N S Radio TV Interference Problems." This booklet VOLTAGE" INSIDE PERSONNEL. NAPicon shows on the display to indicatethe function is activated.3. To check remaining nap time, press NAPonce to show the time on the display4. Snooze function canbe usedrepeatedly up to 30 minutes(default: 9 minutes). Switching Band Slide the AM/FM switch on the back of the unit to select FM or AM band. Can You Chip In?Dear Patron: Please don't scroll past this. M  xico, D.F. Telfono: 52-55-11-020360 RFC: CTM-980723-KS5 EXPORTE Thomson Inc. Important Information Technical Information • Make sure that you keep your set away from water and high product: Clock Radio temperatures. It allows you to set two alarms, each with the option to wake up to a beep, music from the radio, or no sound. The time decrements or incrementswill follow by a faster rate when you pressand hold the buttons. (PST) (refer to the maps on the right). When the (reconnected), the Digital Display will blink to battery backup functions, the digital indicate that power was interrupted and you display will not light, however, the should readjust the time and alarm settings. The clock time shows after a few WAKE2/ WAKE2/ WAKE2/ is at the lock WAKE2/ WAKE2/ seconds if no button is pressed. (EST) When tuning in FM stations, you may Brightness Control Clock time and radio frequency are display on the display area at the front of the unit. ... The RCA RC142 is a user-friendly clock radio with multiple features. volume will increase gradually to Sleep Function 1. Corresponding lights on the front of the unit.Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 orWAKE 2 position to check the currentlyThis device complies with Part 15 of the FCCRules. SLEEP, temporarily. Nap Function TM Operation This function wakes you up after a short Switching Off Wake Function period of time (from 10 minutes to 2 Press WAKE - OFF 1 or 2 repeatedly on hours). icon shows on the display to indicate the function is activated. FCC Information Safety Information English For Your Safety FCC Information This device complies with Part 15 of the FCC The AC power plug is polarized (one blade is wider than the Rules. The timedecrements or increments will followby a faster rate when you press andhold the buttons. The alarm or radio will be onagain when the snooze period is over. C.P. 06700. TUNING - selects radio frequencies. Note: we recommend that you replace the batteries every 2-3 years. Do not attempt to bypass thisCaution: The screw fastening power cord at thebottom enclosure is served as a means of powercord strain relief. User manuals, WAKE U-WAKE U-WAKE U-WAKE You may be woken up by radio or alarm. P.O. Box 1976 Indianapolis, IN 46206 - 1976   2006 Thomson Inc. change. Radio Selecting Radio Mode Press RADIO/AUX to switch on radio. Remove battery compartment door(located at the bottom of the radio)by applying thumb pressure to the tab on battery door and then lift the door out and off the cabinet.2. Insert 2 AA batteries (included).3. Auto Clock Set TIME ZONE - slide to select time zone corresponds to your location. The alarm Press SNOOZE on the top of the unit. Listening to Auxiliary Source 1. Roma. The on the top of the unit to WAKE 1 or will be off by pressing SNOOZE, NAP, wake alarm or radio will be switched off WAKE 2 position. AM Antenna A built-in ferrite rod antenna eliminates the need for an outside antenna for AM reception. • Plug the unit into a different wall outlet so Place of Purchase: that the unit and the equipment receiving interference are on different branch circuits. Slide BRIGHTNESS SWITCH on the back of the unit to HI (high) or LO (low) position to adjust the brightness. If it still does not fit, contact a qualified or modifications not expressly approved by Thomson Inc. After AC power is restored(reconnected), the Digital Display will blink toindicate that power was interrupted and youshould readjust the time and alarm settings.Power is fed to the unit evenwhen it is not functioning. Turn on the unit and your auxiliary source. • Minimum distances (2cm) around the apparatus for sufficient ventilations. Operation is subject to the following twconditions: (1) This device may not cause harmfulinterference, and (2) this device must accept anyinterference received, including interference that may cause undesired operation. In accordance with FCC requirements, changesor modifications not expressly approved byThomson Inc. Do not loosen or throw this in the event that service should be required, youmay need the model number. The AUX indicator on the front will turn on, function of alarm still occurs during the power interruption if remaining battery power is adequate. • Attention should be drawn to the environmental aspects of battery disposal. View and Download RCA RP5420 user manual online. The alarmwill be off by pressing SNOOZE, NAP,SLEEP, REV or FWD until thesnooze period is over. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOOZE.2. Press REV or FWD to set thequiet period. All you have to do is to plug this clock for power andcurrent time will be shown automatically.However, the batteries can also beexhausted and we recommend that youreplace the batteries every 2-3 years.Clock time and radio frequency aredisplay on the display area at the front ofthe unit. is available from the U.S. Government Printing SEE MARKING ON BOTTOM / BACK OF PRODUCT Office, Washington, DC 20402. Normal operation will GEFahr EINES resume after AC power is restored so you ELEKTRISCHEN SCHLAGS will not have to reset the time or the alarm. WARNING: Please avoid playing with these buttons built-in automatic time set system is AM/FM - selects between AM and FM bands. Right View -VOLUME+ - adjusts volume. REV or FWD to set the quiet period. The Internet Archive is working to keep the record straight by recording government websites, news publications, historical documents, and more. You may slide the TIME ZONE selector at SNOOZE - enters snooze mode where the back of the unit to Eastern (EST), alarm will quiet but sound again once the RCA Clock Operating guides and Service manuals, could void the user's authority and this device generates and uses radio frequency(RF) energy, and if not installed and usedproperly, this equipment may cause interference to radio and television reception.If this equipment does cause interference to radio or television reception (which you candetermine by unplugging the unit), try to correctthe interference by one or more of the following • Re-orient the receiving antenna (that is, theantenna for the radio or television that is "receiving" (the interference). • Move the unit away from the equipment thatis receiving interference. • Plug the unit into a different wall outlet sothat the unit and the equipment receivinginterference are on different branch circuits.If these measures do not eliminate theinterference, please consult your dealer or anexperienced radio/television technician foradditional suggestions. 2. After this, the wakefunction will turn off until the next day.Set the "quiet" period as follow:1. (see respective wake time. You do not have to set the clock time as a DST - turns daylight saving function on or off. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOOZE.2. Press REV or FWD to set thequiet period. All you have to do is to plug this clock for power andcurrent time will be shown automatically.However, the batteries can also beexhausted and we recommend that youreplace the batteries every 2-3 years.Clock time and radio frequency aredisplay on the display area at the front ofthe unit. is available from the U.S. Government Printing SEE MARKING ON BOTTOM / BACK OF PRODUCT Office, Washington, DC 20402. Normal operation will GEFahr EINES resume after AC power is restored so you ELEKTRISCHEN SCHLAGS will not have to reset the time or the alarm. WARNING: Please avoid playing with these buttons built-in automatic time set system is AM/FM - selects between AM and FM bands. Right View -VOLUME+ - adjusts volume. REV or FWD to set the quiet period. The Internet Archive is working to keep the record straight by recording government websites, news publications, historical documents, and more. You may slide the TIME ZONE selector at SNOOZE - enters snooze mode where the back of the unit to Eastern (EST), alarm will quiet but sound again once the RCA Clock Operating guides and Service manuals, could void the user's authority and this device generates and uses radio frequency(RF) energy, and if not installed and usedproperly, this equipment may cause interference to radio and television reception.If this equipment does cause interference to radio or television reception (which you candetermine by unplugging the unit), try to correctthe interference by one or more of the following • Re-orient the receiving antenna (that is, theantenna for the radio or television that is "receiving" (the interference). • Move the unit away from the equipment thatis receiving interference. • Plug the unit into a different wall outlet sothat the unit and the equipment receivinginterference are on different branch circuits.If these measures do not eliminate theinterference, please consult your dealer or anexperienced radio/television technician foradditional suggestions. 2. After this, the wakefunction will turn off until the next day.Set the "quiet" period as follow:1. (see respective wake time. You do not have to set the clock time as a DST - turns daylight saving function on or off. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOOZE.2. Press REV or FWD to set thequiet period. All you have to do is to plug this clock for power andcurrent time will be shown automatically.However, the batteries can also beexhausted and we recommend that youreplace the batteries every 2-3 years.Clock time and radio frequency aredisplay on the display area at the front ofthe unit. is available from the U.S. Government Printing SEE MARKING ON BOTTOM / BACK OF PRODUCT Office, Washington, DC 20402. Normal operation will GEFahr EINES resume after AC power is restored so you ELEKTRISCHEN SCHLAGS will not have to reset the time or the alarm. WARNING: Please avoid playing with these buttons built-in automatic time set system is AM/FM - selects between AM and FM bands. Right View -VOLUME+ - adjusts volume. REV or FWD to set the quiet period. The Internet Archive is working to keep the record straight by recording government websites, news publications, historical documents, and more. You may slide the TIME ZONE selector at SNOOZE - enters snooze mode where the back of the unit to Eastern (EST), alarm will quiet but sound again once the RCA Clock Operating guides and Service manuals, could void the user's authority and this device generates and uses radio frequency(RF) energy, and if not installed and usedproperly, this equipment may cause interference to radio and television reception.If this equipment does cause interference to radio or television reception (which you candetermine by unplugging the unit), try to correctthe interference by one or more of the following • Re-orient the receiving antenna (that is, theantenna for the radio or television that is "receiving" (the interference). • Move the unit away from the equipment thatis receiving interference. • Plug the unit into a different wall outlet sothat the unit and the equipment receivinginterference are on different branch circuits.If these measures do not eliminate theinterference, please consult your dealer or anexperienced radio/television technician foradditional suggestions. 2. After this, the wakefunction will turn off until the next day.Set the "quiet" period as follow:1. (see respective wake time. You do not have to set the clock time as a DST - turns daylight saving function on or off. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOOZE.2. Press REV or FWD to set thequiet period. All you have to do is to plug this clock for power andcurrent time will be shown automatically.However, the batteries can also beexhausted and we recommend that youreplace the batteries every 2-3 years.Clock time and radio frequency aredisplay on the display area at the front ofthe unit. is available from the U.S. Government Printing SEE MARKING ON BOTTOM / BACK OF PRODUCT Office, Washington, DC 20402. Normal operation will GEFahr EINES resume after AC power is restored so you ELEKTRISCHEN SCHLAGS will not have to reset the time or the alarm. WARNING: Please avoid playing with these buttons built-in automatic time set system is AM/FM - selects between AM and FM bands. Right View -VOLUME+ - adjusts volume. REV or FWD to set the quiet period. The Internet Archive is working to keep the record straight by recording government websites, news publications, historical documents, and more. You may slide the TIME ZONE selector at SNOOZE - enters snooze mode where the back of the unit to Eastern (EST), alarm will quiet but sound again once the RCA Clock Operating guides and Service manuals, could void the user's authority and this device generates and uses radio frequency(RF) energy, and if not installed and usedproperly, this equipment may cause interference to radio and television reception.If this equipment does cause interference to radio or television reception (which you candetermine by unplugging the unit), try to correctthe interference by one or more of the following • Re-orient the receiving antenna (that is, theantenna for the radio or television that is "receiving" (the interference). • Move the unit away from the equipment thatis receiving interference. • Plug the unit into a different wall outlet sothat the unit and the equipment receivinginterference are on different branch circuits.If these measures do not eliminate theinterference, please consult your dealer or anexperienced radio/television technician foradditional suggestions. 2. After this, the wakefunction will turn off until the next day.Set the "quiet" period as follow:1. (see respective wake time. You do not have to set the clock time as a DST - turns daylight saving function on or off. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOOZE.2. Press REV or FWD to set thequiet period. All you have to do is to plug this clock for power andcurrent time will be shown automatically.However, the batteries can also beexhausted and we recommend that youreplace the batteries every 2-3 years.Clock time and radio frequency aredisplay on the display area at the front ofthe unit. is available from the U.S. Government Printing SEE MARKING ON BOTTOM / BACK OF PRODUCT Office, Washington, DC 20402. Normal operation will GEFahr EINES resume after AC power is restored so you ELEKTRISCHEN SCHLAGS will not have to reset the time or the alarm. WARNING: Please avoid playing with these buttons built-in automatic time set system is AM/FM - selects between AM and FM bands. Right View -VOLUME+ - adjusts volume. REV or FWD to set the quiet period. The Internet Archive is working to keep the record straight by recording government websites, news publications, historical documents, and more. You may slide the TIME ZONE selector at SNOOZE - enters snooze mode where the back of the unit to Eastern (EST), alarm will quiet but sound again once the RCA Clock Operating guides and Service manuals, could void the user's authority and this device generates and uses radio frequency(RF) energy, and if not installed and usedproperly, this equipment may cause interference to radio and television reception.If this equipment does cause interference to radio or television reception (which you candetermine by unplugging the unit), try to correctthe interference by one or more of the following • Re-orient the receiving antenna (that is, theantenna for the radio or television that is "receiving" (the interference). • Move the unit away from the equipment thatis receiving interference. • Plug the unit into a different wall outlet sothat the unit and the equipment receivinginterference are on different branch circuits.If these measures do not eliminate theinterference, please consult your dealer or anexperienced radio/television technician foradditional suggestions. 2. After this, the wakefunction will turn off until the next day.Set the "quiet" period as follow:1. (see respective wake time. You do not have to set the clock time as a DST - turns daylight saving function on or off. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOOZE.2. Press REV or FWD to set thequiet period. All you have to do is to plug this clock for power andcurrent time will be shown automatically.However, the batteries can also beexhausted and we recommend that youreplace the batteries every 2-3 years.Clock time and radio frequency aredisplay on the display area at the front ofthe unit. is available from the U.S. Government Printing SEE MARKING ON BOTTOM / BACK OF PRODUCT Office, Washington, DC 20402. Normal operation will GEFahr EINES resume after AC power is restored so you ELEKTRISCHEN SCHLAGS will not have to reset the time or the alarm. WARNING: Please avoid playing with these buttons built-in automatic time set system is AM/FM - selects between AM and FM bands. Right View -VOLUME+ - adjusts volume. REV or FWD to set the quiet period. The Internet Archive is working to keep the record straight by recording government websites, news publications, historical documents, and more. You may slide the TIME ZONE selector at SNOOZE - enters snooze mode where the back of the unit to Eastern (EST), alarm will quiet but sound again once the RCA Clock Operating guides and Service manuals, could void the user's authority and this device generates and uses radio frequency(RF) energy, and if not installed and usedproperly, this equipment may cause interference to radio and television reception.If this equipment does cause interference to radio or television reception (which you candetermine by unplugging the unit), try to correctthe interference by one or more of the following • Re-orient the receiving antenna (that is, theantenna for the radio or television that is "receiving" (the interference). • Move the unit away from the equipment thatis receiving interference. • Plug the unit into a different wall outlet sothat the unit and the equipment receivinginterference are on different branch circuits.If these measures do not eliminate theinterference, please consult your dealer or anexperienced radio/television technician foradditional suggestions. 2. After this, the wakefunction will turn off until the next day.Set the "quiet" period as follow:1. (see respective wake time. You do not have to set the clock time as a DST - turns daylight saving function on or off. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOOZE.2. Press REV or FWD to set thequiet period. All you have to do is to plug this clock for power andcurrent time will be shown automatically.However, the batteries can also beexhausted and we recommend that youreplace the batteries every 2-3 years.Clock time and radio frequency aredisplay on the display area at the front ofthe unit. is available from the U.S. Government Printing SEE MARKING ON BOTTOM / BACK OF PRODUCT Office, Washington, DC 20402. Normal operation will GEFahr EINES resume after AC power is restored so you ELEKTRISCHEN SCHLAGS will not have to reset the time or the alarm. WARNING: Please avoid playing with these buttons built-in automatic time set system is AM/FM - selects between AM and FM bands. Right View -VOLUME+ - adjusts volume. REV or FWD to set the quiet period. The Internet Archive is working to keep the record straight by recording government websites, news publications, historical documents, and more. You may slide the TIME ZONE selector at SNOOZE - enters snooze mode where the back of the unit to Eastern (EST), alarm will quiet but sound again once the RCA Clock Operating guides and Service manuals, could void the user's authority and this device generates and uses radio frequency(RF) energy, and if not installed and usedproperly, this equipment may cause interference to radio and television reception.If this equipment does cause interference to radio or television reception (which you candetermine by unplugging the unit), try to correctthe interference by one or more of the following • Re-orient the receiving antenna (that is, theantenna for the radio or television that is "receiving" (the interference). • Move the unit away from the equipment thatis receiving interference. • Plug the unit into a different wall outlet sothat the unit and the equipment receivinginterference are on different branch circuits.If these measures do not eliminate theinterference, please consult your dealer or anexperienced radio/television technician foradditional suggestions. 2. After this, the wakefunction will turn off until the next day.Set the "quiet" period as follow:1. (see respective wake time. You do not have to set the clock time as a DST - turns daylight saving function on or off. The time decrements or increments will follow by a faster rate when you press and hold the buttons. Never use solvents.When AC power is interrupted (disconnected)for a short period of time, both time andalarm settings will change (unless batteriesare installed). Radio This operation allows extra sleep time 1. • Move the unit away from the equipment that Date of Purchase: is receiving interference. EN/F/E It is important to read this instruction book prior to using your new product for the first time. You can ... The clock also features dual alarms, allowing users to set different wake-up times for different days of the week. We understand that not everyone can donate right now, but if you can afford to contribute this Thursday, we promise it will be put to good use. Press REV or FWD to set the snooze period is over. A C C O M P A N Y I N G Guide. To check remaining nap time, press NAP once to show the time on the display briefly. • To prevent personal injury, do not IMPORTER Comercializadora Thomson de M  xico, S.A. de C.V. reverse any batteries. 3. seconds. To turn off the wake alarm or radio hold the buttons. Corresponding automatically. Normal operation willresume after AC power is restored so youwill not have to reset the time or theinstall battery as follows:1. AM or PM icon will3. Radio frequency shows on the display. This device generates and uses radio frequency safety feature. Can You Chip In? Slide the switch /WAKE1/WAKE2/on the top of the unit to positionImportant InformationFCC Information Safety InformationIt is important to read this instruction book prior to using your new product for the first time.DO NOT EXPOSE THIS PRODUCTSEE MARKING ON BOTTOM / BACK OF PRODUCTThis unit allows two wake times to be set.1. Slide the switch /WAKE1/WAKE2/on the top of the unit to WAKE 1 or2. RP5420 clock radio pdf manual download. The clock time shows after a fewseconds if no button is pressed. We build and maintain all our own systems, but we don't charge for access, sell user information, or run ads. Insert 2 AA batteries (included). unit and use REV or FWD to set the duration up to 2 hours. • The ventilation should not be impeded by covering the ventilation opening with items, such as newspaper, table-cloths, curtains, etc. If theplug will not go into the outletcompletely, turn the plug overand try to insert it the otherway. Always tune carefullyat the loudest and clearest point.A built-in ferrite rod antenna eliminates the need for an outside antenna for AMreception. Press and hold SNOO